

# BeneFusion eSP (TCI)

Syringe Pump

Data Sheet



## Physical Specifications

Weight	≤ 1.6kg
Size	≤ 257x 150 x73mm
Screen	3.5 inch touchscreen TFT color LCD, 200x400 pixels
Brightness	1-8 levels, adjustable
Display	Drug name, Effect-site concentration (Ce), Current rate, Target concentration (Cpt/Cet), Plasma concentration (Cp), Awake time, TCI trend

## Parameters Specifications

Accuracy	≤ ±1.8%
Mode	TCI Mode, TIVA Mode, Rate mode, Dose Mode, Dose Time Mode, Time mode, Sequential Mode, Intermittent Mode, Loading Dose Mode, Ramp Mode, Micro-infusion Mode
PK model	Propofol- Marsh: Plasma/Effect Site; Propofol- Schnider: Plasma/Effect Site; Propofol-Kataria (Pedia):Plasma; Propofol-Paedfusor (Pedia): Plasma; Propofol-Eleveld: Plasma/Effect Site; Propofol-Cortinez: Plasma; Remifentanil-Minto: Plasma/Effect Site Remifentanil-Eleveld: Plasma/Effect Site Sulfentanil-Gepts: Plasma/Effect Site Alfentanil-Maitre: Plasma/Effect Site
Flow rate	0.01-2300ml/h
Increment	0.01ml/h (0.01-99.99ml/h); 0.1ml/h (100.0-999.9ml/h); 1ml/h (1000-2300ml/h)
Preset volume (VTBI)	0.01 ml - 9999.99 ml, increment: 0.01mL
Preset time	00:00:01-99:59:59, adjustable
Accumulated volume	0.00 ml - 99999.99 ml
KVO	0.01 to 50ml/h; increment: 0.01ml/h
Purge rate	0.01-2300ml/h
Bolus rate	0.01-2300ml/h (automatic or manual)
Occlusion detection	50-1125mmHg (15 levels selectable, respectively are 50, 150, 225, 300, 375, 450, 525, 600, 675, 750, 825, 900, 975, 1050, 1125mmHg) default is 450mmHg; 4 units of pressure selectable: mmHg/ kPa/ bar/ psi
Anti-bolus	Unexpected bolus reduced when the occlusion occurs
Dose rate units	ng/kg/min, ng/kg/h, ng/kg/24h, ug/kg/min, ug/kg/h, ug/kg/24h, mg/kg/min, mg/kg/h, mg/kg/24h, g/kg/min, g/kg/h, g/kg/24h, mU/kg/min, mU/kg/h, mU/kg/24h, U/kg/min, U/kg/h, U/kg/24h, kU/kg/min, kU/kg/h, kU/kg/24h, EU/kg/min, EU/kg/h, EU/kg/24h, mmol/kg/min, mmol/kg/h, mmol/kg/24h, mol/kg/min, mol/kg/h, mol/kg/24h, mcal/kg/min, mcal/kg/h, mcal/kg/24h, cal/kg/min, cal/kg/h, cal/kg/24h, kcal/kg/min, kcal/kg/h, kcal/kg/24h, mEq/kg/min, mEq/kg/h, mEq/kg/24h
Screen lock	Support password-protected screen lock
Auto-lock time	1 - 5 minutes selectable; ON/OFF switchable

Drug library	Up to 5000 drugs; 50 categories (optional); 30 care areas/departments, support color-coding drug name
History log	Up to 3500 records
Volume collection	Available in 4 methods: 24H total, current total, period, timing volume
DERS (Dose Error Reduction System)	Available; definition of dose limits; automatic alarms when reaching dose limits

## Syringes

Compatibility	1/2/3/5/10/20/30/50/60ml; automatic recognition of syringe size
---------------	--

## Alarms

Type	Audible and visual alarm
Level	High: Occlusion/ Syringe empty/ Syringe Disengaged/ Plunger Grippers Error/ Battery Depleted/ VTBI Complete/ KVO Finish/ Relay Invalid/ System Error/ No Syringe Low: KVO Running/ Battery in Use/ Battery Error/CMS/eGW Disconnected/ Standby Time Expired/ Dock Connection Interrupted/ System Time Error/ Relay Invalid Soon/ Time Near End/ Reminder/ Low Battery/ Syringe Near Empty
Sound volume	1-8 levels selectable, default is level 4
Reminder	1-5 minutes selectable; ON/OFF switchable

## Connectivity

Communication USB	Wireless Support drug library import, patient information loading, patient data export, history record export, calibration data import/ export
Multifunctional connector	RS232; nurse call connector; DC adapter
Integration	Synergy with Mindray patient monitor Connect with BeneVision Central Monitoring System

## Battery

Operating time	≥ 5 hours at 5ml/h (≥ 11 hours at 5ml/h for smart battery)
Charging time	≤ 5 hours to full capacity (≤ 6 hours for smart battery)

## Power Supply

Voltage 100-240 V; frequency 50/60Hz; current 0.5-0.21A
---

## Work Environment

Temperature	5-40°C for operating; -30-70 °C for storage
Relative humidity	15-95% for operating; 10-95% for storage
Atmosphere pressure	57.0-107.4 kPa for operating; 16.0-107.4 kPa for storage
Classification	Type CF, Protection Class I, IP33
Stackability	Supported with stack rack, maximum of 3 pumps can be stacked

[www.mindray.com](http://www.mindray.com)

P/N: ENG-BeneFusion eSP (TCI) Datasheet-210285x2P-20251230

©2019 Shenzhen Mindray Scientific Co., Ltd. All rights reserved. Specifications subject to changes without prior notice.

**mindray**  
healthcare within reach